

Bardahl		Castrol		BLU Synthetic		RAVENOL		MORRIS LUBRICANTS	
<b>XTG Gear Oil FE 75W Syntronic</b>		<b>Syntrans Transaxle 75W-90*</b>		<b>75W-90 Technician Series MTF-FS</b>		<b>MTF-3 SAE 75W</b>		<b>LODEXOL MTFE 75W</b>	
Density at 15°C	0.873	Density @ 15°C DIN EN ISO 12185 g/ml	0.866	Specific Gravity @ 15.6	0.871	Density at 20°C g/ml EN ISO 12185	0.846	Density at 15.6oC	0.842
Viscosity at 40°C	40.8	Viscosity, Kinematic 40°C ASTM D445 mm <sup>2</sup> /s	78	Viscosity @ 40 C, CST	93.5			Viscosity @ 40oC, cSt.	31.93
Viscosity at 100°C	6.7	Viscosity, Kinematic 100°C ASTM D445 mm <sup>2</sup> /s	14.8	Viscosity @ 100 C, CST	15.92			Viscosity @ 100oC, cSt.	6.43
Viscosity index	119	Viscosity Index ISO 2909 None	195	Viscosity Index	183			Viscosity Index	159
Pourpoint °C	-44	Pour Point DIN-ISO 3016 °C	-54	Pour Point C	-42	Pourpoint °C DIN ISO 30	-60	Pour Point, oC	-63
Brookfield-viscositeit bij -40°C	75000	Viscosity, Brookfield @ -40°C DIN 51398 mPa.s (cP)	< 50.000					Brookfield at -40oC, mPa.s	8540
Flashpoint COC °C	220	Flash Point, COC DIN-ISO 2592 °C	210	Flash Point C	220			Flash Point (Closed) oC	140
Appearance Visual	Yellow-brown	Appearance Visual	bright & clear	Product Specifications		Colour	braun visual	Colour	Amber
Specifications		Product Performance Claims		Industry Standards				Performance Level	
API GL4		API GL-4+		API GL-4				API GL4	
Toyota 08885-81001 Toyota 08885-81081				Toyota 08885-81001 Toyota 08885-81023		Toyota 08885-81001 Toyota 08885-81081		Toyota 08885-81001 Toyota 08885-81081	